



Berth facilities

12 mooring hooks on 6 dolphins + 4 mooring bollards on dolphins+ 2 (50 t) on the pier	75 t per hook 50t /100t per bollard
<p align="center">Manifold 8 inches (EPG, upriver side) white products : Petrol (gasoline) + diesel Manifold 12 inches (SPBA, downriver side) white products : Jet / petrol (gasoline) / diesel / Heating oil (FOD) Maximum Pressure = 12 bars</p>	
Gangway	Yes (Telescopic gangway conditional)
Bunkering	No Bunkering
Stores	by lorry
Fresh water	available on berth

Vessel berth compatibility criteria

Maximum displacement	50.000 t
Maximum length over all (LOA)	210 m
Minimum length over all (LOA)	100 m
Maximum draft	10.5 m
Under-keel clearance	0.5 m
Maximum beam	-
Maximum air draft	-
Minimum parallel body length required	68 m
High of the pier above chart datum level	7 m
Maxi/mini. allowable manifold height above the water	Manifold 19m above chart datum

Minimum mooring plan requested

	Head/stern lines	45° lines	Breast lines	Spring lines
5000t<dwt<15.000t	3		2	2
15000t<dwt<30.000t	2	2	2	2
30.000t<dwt	3	3	2	2

The mooring remains under the responsibility of the ship's master and the number of lines must be increased if necessary

Berth fire fighting equipment

Fire fighting system	yes
2 foam and water monitors	2000 l/mn each – foam tank 3000 l
Fire extinguishers	powder 9 and 50 kg
Others	fire blanket/fire equipment/sand

Berth anti-pollution equipment

Convention with boatmen company	yes
Antipol installation	yes
Emergency Release Coupling	yes
Shower	yes

Terminal contacts

EPG standard : 0033(0)5 56 77 34 80
SPBA standard : 0033(0)5 56 77 08 20
Berth to control rooms : Walkies-talkies + telephone
Port officer Ambes : mobile phone (24/24h) : 0033(0)664499245
Fresh water service : by watchman

AMBÈS

